



MODEL	X	X/T	X	X/T	X	X/T	X	X/T	X	X/T	G	E	F
0253...06	3"-6"	X/4	6"-9"	X/6	9"-12"	X/8	12"-15"	X/10	15"-16.5"	X/12	0.3125"	0.3125"	0.3125"
0253...10	4"-8"	X/4	8"-12"	X/6	12"-16"	X/8	16"-20"	X/10	16"-23.5"	X/12	0.619"	0.619"	0.619"
0253...15	5"-10.25"	X/4	10.25"-15.25"	X/6	15.25"-20.5"	X/8	20.5"-23.5"	X/10	/	/	0.625"	0.625"	0.625"
0253...20	6"-12"	X/4	12"-17.75"	X/6	17.75"-23.5"	X/8	/	/	/	/	1"	1"	1"
0253...25	7"-14"	X/4	14"-21"	X/6	21"-23.5"	X/8	/	/	/	/	1.25"	1.25"	1.25"
0253...30	8"-16"	X/4	16"-23.5"	X/6	/	/	/	/	/	/	1.5"	1.5"	1.5"

	0253...06	0253...10	0253...15	0253...20	0253...25	0253...30
SPESSORE LAMIERA / METAL SHEET THICKNESS / DICKE DES BLECHS	0.010"-0.042"	0.043"-0.075"	0.076"-0.120"	0.121"-0.164"	0.165"-0.209"	0.210"-0.250"
LUNGHEZZE / LENGTHS / LÄNGEN MIN-MAX (X)	1.2"-16.5"	1.6"-23.5"	1.6"-23.5"	2"-23.5"	2"-23.5"	2"-23.5"
DIAMETRO ROTANTE / ROTATING DIAMETER / Ø BIEGEEINSATZ (D)	0.625"	1"	1.5"	2"	2.5"	3"
LARGHEZZA CORPO / BODY WIDTH / BREITE DES GRUNDKÖRPERS (SW)	1"	1.5"	2"	3"	3.5"	4"
DIST. MIN. ROTANTE-FRONTA / DIST. MIN. ROTATING BODY-FRONT PART / ABSTAND MIN. DREHKÖRPER (SF)	0.5"	0.75"	1"	1.5"	1.75"	2"
DIST. ROTANTE-CHIAVETTA / DIST. ROTATING BODY - WEDGE / ABSTAND DREHKÖRPER (SK)	0.5"	0.75"	1"	1.5"	1.75"	2"
DIST. ROTANTE-BASE (SH) - DIST. BODY-ROTATING BODY / ABSTAND DREHKÖRPER-GRUNDKÖRPER	2"	2"	2.75"	3"	4"	4.5"
INGOMBRO SUPPORTO (L) / HOLDER OVERALL / HÖHE HALTER	0.177"	0.283"	0.439"	0.602"	0.744"	0.913"
DIAMETRI FISSAGGI (H) / DIAMETERS OF THE FIXING / BEFESTIGUNGSDURCHMESSER	1/4 20 UNC	5/16 18 UNC	5/16 18 UNC	1/2 13 UNC	1/2 13 UNC	1/2 13 UNC
POSIZIONE DEI FISSAGGI (E) / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	0.3125"	0.619"	0.625"	1"	1.25"	1.5"
POSIZIONE DEI FISSAGGI (F) / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	0.3125"	0.619"	0.625"	1"	1.25"	1.5"
POSIZIONE DEI FISSAGGI (G) / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	0.3125"	0.619"	0.625"	1"	1.25"	1.5"

Può lavorare anche senza lubrificazione / It works also without lubrication / Es funktioniert auch ohne Schmierung / Il peut fonctionner sans lubrification

SPECIAL GEOMETRIES AND LENGTHS (600 mm+) AFTER CONSULTING NEWSTARK'S TECHNICAL DEPARTMENT

MODELLO D'ORDINE / ORDER EXAMPLE / BESTELLBEISPIEL / MODÈLE DE COMMANDE

MODEL **0253** TYPE BEND **03** Ø DIAMETER **15 (1.5")** LENGTH **500** ANGLE **90°**